

Digitron's 2106 Digital Thermometer has been created to meet the demands of the ever changing **food industry**. It's design and enhanced features ensure a quality performance at all times.

The 2106 includes a **food safe design** keypad to eliminate potential food traps when used in a kitchen environment and also has an instant display reading.

General Specification

| | |
|-------------------------------------|---|
| Operating Temperature: | -10°C to +50°C/+14°F to +122°F |
| Battery Life: | 1-2 hours of continuous use for 2 years. Improved with use of LiCL batteries |
| Battery Type: | 2 x 'AA' Alkaline or LiCl |
| Display: | 12.8mm/0.5" custom LCD |
| Overrange/underrange: | 'Out' displayed |
| Environmental Specification: | IP67 |
| Auto Switch-off Time: | 5 minutes - can be over-riden by pressing the 'Hold' button when switching the unit on |
| Sensor Type: | T Type Thermocouple |
| Resolution: | 0.1 from -199.9°C to +199.9°C |
| Accuracy All ±1 digit: | ±0.2°C/ 0.4°F over range -20°C to +70 °C -4°F to +158°F ±0.1% rdg ±0.2°C/0.4°F elsewhere <i>(Excluding probe error - Refer to IEC 60584)</i> |
| Range: | -250°C to +400°C/-418°F to +752° F |
| Dimensions: | 155 x 67 x 40mm/6.1 x 2.6 x 1.6" |
| Weight: | 180g/4oz |
| Warranty: | 2 years |



2106T

A selectable °C/°F version instrument available on request

For other options, please contact us digitronsales@rototherm.co.uk or +44 (0)1656 740551

Key Features and Benefits

- Food Safe Keypad
- Fast Response Display
- Improved Battery Life
- Selectable Auto Switch - Off
- IP67 Waterproof
- Hold facility

Main Applications

A **world leader** in digital thermometers, Rototherm has become the standard for accurate and reliable measurement across the following industries:



Commercial & Domestic
HVAC



Pharmaceutical



Transport



Food & Beverage

Technical Certification

- Certificate of conformity
- Factory Test Certificate
- Factory Calibration Certificate

Export Documentation


- Certificate of Origin
- EUR1
- ATR

Calibration and After-Sales Support

- Fully trained field service personnel
- Use of UKAS certified calibration equipment
- 5 day turnaround
- Fixed pricing
- Approved manufacturer parts
- Full post-service reports
- 2 year warranty



ISO9001:2008
FM11958



For more information, please contact our service team
digitronservice@rototherm.co.uk