

2106 IVF Model

Digitron's 2106T hand-held **Digital IVF Thermometer** has been designed to meet the demands of **fertility clinics**. The unit is made up of a 2106T handheld unit and a specially designed Embryo Microprobe.

The effective control of temperature is an essential requisite in fertility clinics and the 2106T IVF Thermometer ensures this need is consistently met. In addition it is IP67 rated and comes with a protective rubber boot for additional protection and stability.

A 'hold' facility, improved battery life and selectable auto switch-off are standard on the model.

General Specification

Operating Temperature:	-10°C to +50°C/+14°F to +122°F
Battery Life:	1-2 hours of continuous use for 2 years. Improved with use of LiCL batteries
Battery Type:	2 x 'AA' Alkaline or LiCl
Display:	12.8mm/0.5" custom LCD
Overrange/underrange:	'Out' displayed
Environmental Specification:	IP67
Auto Switch-off Time:	5 minutes - can be over-ridden by pressing the 'Hold' button when switching the unit on
Sensor Type:	T Type Thermocouple
Resolution:	0.1 from -199.9°C to +199.9°C
Accuracy All ±1 digit:	±0.2°C/ 0.4°F over range -20°C to +70 °C -4°F to +158°F ±0.1% rdg ±0.2°C/0.4°F elsewhere (Excluding probe error - Refer to IEC 60584)
Range:	-250°C to +400°C/-418°F to +752° F
Dimensions:	155 x 67 x 40mm/6.1 x 2.6 x 1.6"
Weight:	180g/4oz
Warranty:	1 year



**DG-IVF-KIT
Model**

A selectable °C/°F version instrument available on request

For other options, please contact us digitronsales@rototherm.co.uk or +44 (0)1656 740551

Key Features and Benefits

- Sealed Silicone Rubber Keypad
- Fast Response Display
- Improved Battery Life
- Selectable Auto Switch - Off
- IP67 Waterproof
- Hold facility

Main Applications

A **world leader** in digital thermometers, Rototherm has become the standard for accurate and reliable measurement across the following industries:



**Pharmaceutical &
Medical**

Technical Certification

- Certificate of conformity
- Factory Test Certificate
- Factory Calibration Certificate

Export Documentation


- Certificate of Origin
- EUR1
- ATR

Calibration and After-Sales Support

- Fully trained field service personnel
- Use of UKAS certified calibration equipment
- 5 day turnaround
- Fixed pricing
- Approved manufacturer parts
- Full post-service reports
- 1 year warranty



ISO9001:2008
FM11958



For more information, please contact our service team
digitronservice@rototherm.co.uk